

PHASE MONITORS

THREE PHASE MOTOR **PROTECTION**

MADE IN THE U.S.A.

BASIC MODELS:

DPDT / Surface Mount

002-230-123 002-480-123

UL FILE #E101681

PROTECTS AGAINST:

Under Voltage Phase Loss Phase Reversal Phase Unbalance (Optional Over Voltage)




OPERATION

When proper voltage is connected to the phase monitor the internal relay will be energized and the LED will come on steady. An abnormal condition will cause the LED to blink during the trip delay. When the trip delay has expired the internal relay will be de-energized. The LED will then provide a series of pulses that indicate which fault condition is present. When conditions return to normal, the LED will blink during the reset delay. When the reset delay has expired, the LED will come on steady and the internal relay will be energized. The reset delay is also active immediately after power is turned on to the unit.

These units can be used on Delta or Wye systems, 50/60 Hz.

Ø0.185" 3.25" 3.70"



3.60

CONDITION	A	В	C
NORMAL		1	
TRIP or RESET	1	3	5
OVERVOLTAGE	7 8	9	10 11 12
Ø UNBALANCE Ø REVERSAL	1,	•	111
	NORMAL TRIP or RESET UNDERVOLTAGE OVERVOLTAGE Ø UNBALANCE	NORMAL TRIP or RESET UNDERVOLTAGE OVERVOLTAGE Ø UNBALANCE 7 8	NORMAL TRIP or RESET UNDERVOLTAGE OVERVOLTAGE Ø UNBALANCE 7 8 9

SPECIFICATIONS

Under Voltage:

Trip: - 15% of Setting for 230V (-10% for 480V) Reset: - 12% of Setting for 230V (-8% for 480V)

Over Voltage:

+ 15% of Setting for 230V (+10% for 480V) Trip: + 12% of Setting for 230V (+8% for 480V) Reset:

Phase Unbalance:

7% with 5 Second Trip Delay Trip:

15% with 1 Second Trip Delay

Reset:

Trip Delay: 5 Seconds (Delay is Reduced to 1 Second

if Phase Unbalance is 15% or Greater)

2 Seconds Standard (See Options) Reset Delay: 200V to 240V or 425V to 525V Voltage Range:

Output Rating: 10A Resistive @ 240VAC 6A Inductive @ 240VAC

-40°C to +50 °C Operating Temp: Storage Temp: -45°C to +85 °C Enclosure: White Lexan

ORDERING INFORMATION

002 - XXX - 12 3 - XXXXX Product Type ☐ Operating Voltage -(230,480)Relay Type (DPDT) -Base (Surface Mount) Options:

OV - Over Voltage

G5 - 5 Second Reset Delay G10 - 10 Second Reset Delay G20 - 20 Second Reset Delay G30 - 30 Second Reset Delay G60 - 60 Second Reset Delay